



ECP2050 / ECP2200 / ECP2300

PREPARATIVE HPLC PUMPS is a series of three pumps with a flow-rate range up to 50, 250 and 300 ml/min. These pumps work as isocratic pump and together with Gradient Box also as gradient pump.

ECB2007, ECB2007PC (ECB2005, ECB2005PC) Gradient Box is equipped with four way gradient mixing valve and must be ordered together with the pump.

These pumps are suited for preparative applications in liquid chromatography. They are designed with main and auxiliary pump heads connected in parallel with a piston diameter of 3/8". New sophisticated unit allows achieving a precise low-pressure gradient, i.e. gradual changes of solvent composition by mixing up to four liquids at the pump's entry. It is also possible to predefine percentage of composition when using the pump in isocratic mode. The gradient profile can be defined from computer or manually using display and keypad. There are many improvements which make pumps more reliable include a new learning algorithm for pulsation suppression; leakage sensor etc.

When necessary, it is possible to use back washing of pistons (e.g. when using buffered mobile phase). Pump is supported by ECOMAC and Clarity software. All pumps are delivered with GFP (PTFE) seals as default, recommended optimal seals are UHMW-PE seals, ask for more information.

TECHNICAL PARAMETERS:	ECP2050	ECP2200	ECP2300
Part number	ACC0000X	ACHE000X	ACE0000X
Flow rate	0.1 – 50 ml/min	0.5 – 250 ml/min	0.6 – 300 ml/min
Maximum operating pressure	30 MPa (4351 psi)	30 MPa (4351 psi) up to 100 ml/min; 15 MPa (2176 psi) at 250 ml/min	15 MPa (2176 psi)
Precision of pressure measurement	± 2%		
Flow rate setting	0.1 ml/min steps	0.1 ml/min steps	0.1 ml/min steps
Repeatability of flow rate adjusting*	± 0.5 %	± 1 %	± 0.5 %
Accuracy of flow rate setting*	± 2 %		
Upper pressure limit (MPa)	1– 30 (4351 psi)	1– 30 (4351 psi)	1– 15 (2176 psi)
Wetted materials	stainless steel, PEEK, TefzelTM, PE, ceramic, seals		
Control	RS232, Ethernet(LAN), USB		
Power supply	100-240V 50/60Hz 100VA	100-240V 50/60Hz 250VA	100-240V 50/60Hz 200VA
Supported Gradient Box	ECB2007, ECB2007PC	ECB2005, ECB2005PC	ECB2005, ECB2005PC
Dimensions (W x H x D)	280 x 135 x 498 mm (11.02 x 5.12 x 18.23 in)		
Weight	12 kg (26,5 lb)	13.5 kg (30 lb)	13 kg (28.7 lb)
Output capillary outer diameter	1/16"	1/8"	1/8"
Input tubing outer diameter	1/8"	3/16"	3/16"

*10 ml/min. 12 MPa H₂O (ECP2050), 100 ml/min 15 MPa H₂O (ECP2200), 150 ml/min. 7.5 MPa H₂O (ECP2300)